According to 91/155/EWG Series 700-032

Date of issue / revised : 09-11-2005

Page 1 of 4

1.	IDENTIFICATION OF SUBSTANCE, PREPARATION AND COMPANY					
	TRADE	NAME	SERIES 700-03	2		
	INTENDED USE		ANTISTATIC ADDITIVE FOR GROUP 700			
	MANUFACTURER		PRINTCOLOR SCREEN LTD. CH-8965 BERIKON TEL ++41-(0)56-648 85 85 FAX ++41-(0)56-648 85 00			
2.	EMERGENCY INFORMATION		TELEPHONE NUMBER ++41-(0)1-2515151			
	 2.1 CHEMICAL CHARACTERISTICS OF PRODUCT: MIXTURE OF SOLVENTS WITH POLYOLEFINES 2.2 SUBSTANCES PRESENTING A HEALTH HAZARD WITHIN THE MEANING OF GUIDE-LINES NO.67/548/EC OR ASSIGNED OCCUPATIONAL EXPOSURE LIMITS 					
	CAS-No	DESIGNATION	According to EC Guide-Lines	CONCENTRA- TION WEIGHT-%	DANGER SYMBOL LETTER	R-Phrases (*)
	64742-95-6	SOLVENT NAF	PHTHALINE LIGHT	< 80	Xn, N	10-20-51/53-65
	(*) CLEAR TEX	T OF R- PHRASE	ES SEE SECTION 15 AND 16			
3.	HAZARDS	HAZARDS IDENTIFICATION				
	DANGER SIGN SPECIAL DANGER ADVICE FOR PERSONS AND ENVIRONMENT		HARMFUL, DANGEROUS FOR THE ENVIRONMENT Flammable Harmful: may cause lung damage if swallowed Toxic for aquatic organisms, may cause long-term adverse effects in the aquatic environment Harmful by inhalation			
4.	FIRST AID MEASURES					
	GENERAL		In all cases of doubt or if sym by mouth to an unconscio contaminated clothing.			
	INHALATION		Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing ba mouth. If unconscious, place in the recovery position and seek medical advice.			
	SKIN CONTACT		Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skincleaner. DO NOT USE SOLVENTS OR THINNER.			
	EYE CONTACT		Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.			
			tain immediate r	iate medical attention. Keep at rest. Do NOT		
5.	FIRE FIGHTING MEASURES					
	EXTINGUISHIN		Alashal registent form CO.	audar water en	rov/mist	
	RECOMMENDI		Alcohol resistant foam, CO ₂ , powder, water spray/mist			
	EXTINGUISHING MEDIA		Waterjet			
	SPECIAL PROTECTION		Appropiate breathing apparatus may be required			
	RECOMMEND	ATIONS	Fire will produce dense blac (see Section 10). Decomposit contained breathing apparatu fire with water spray. Do not courses.	ion products ma us may be requi	y be a hazaro ired. Cool clo	d to health. Appropriate self- osed containers exposed to

According to 91/155/EWG Series 700-032

Date of issue / revised : 09-11-2005

Page 2 of 4

6.	ACCIDENTAL RELEASE MEASURES						
	PERSONAL PRECAUTIO	IS Exclude sources of ignition and ver personnel. Avoid breathing vapours. Sections 7 and 8.					
	ENVIRONMENTAL PRECAUTIONS	Do not allow to enter drains or water co lakes and drains or soil, inform the respo		s rivers,			
	METHODS FOR CLEANIN UP / COLLECTING	G Contain and collect spillages with non-co earth, vermiculite, diatomaceous earth disposal in accordance with the waste re	and place in a suitable conta				
7.	HANDLING AND STORAGE						
	HANDLING						
	INFORMATION FOR SAFE HANDLING	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations exceeding the occupational exposure limits. Moreover, the product should only be used in areas which have been cleared from direct light, fire and other sources of ignition. The product may charge itself electro-statically. Electrical equipment should be protected properly. When pouring the product into other containers, only ground mains should be used. It is recommended to wear antistatic clothing and foot wear. Use spark-proof tools. Avoid any contact with eyes or skin. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Follow legal protective and safety instructions.					
	INFORMATION ABOUT PROTECTION AGAINST EXPLOSIONS AND FIRES	Vapours are heavier than air and may sread along floors. They may form explosive mixtures in combination with air. Preparations may charge electrostatically: Always use earthing leads when transferring from one container to another.					
	STORAGE						
	REQUIREMENTS FOR STORAGE ROOMS AND CONTAINERS ADVICE FOR COMBINED	Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: Container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. No ressurized container. Store seperately from strong acid and alkaline materials as well as from oxidizing					
STORAGE agents. FURTHER ADVICE FOR Store at a cool and well ventilated place. Avoid heating and dire STORAGE from flammable matters and observe instructions on the la containers of same material as the original one. store		structions on the labels. Always					
8.	EXPOSURE CONTR	OL / PERSONEL PROTECTION					
	ENGINEERING MEASURES						
	uld be achieved by use of local ntain concentrations of particulate suitable respiratory protective eq	s and/or uipment					
		ICAL VALUES THAT REQUIRE MONITORING AT T	· · ·				
		SIGNATION ACCORDING TO EC GUIDE-LINES	OCCUPATIONAL EXPOSURE LIMITS 50	UNIT ppm			
	The above values have beer SUVA/Switzerland regarding	taken from the valid list (f.e.TRGS 900) of the Federa	I Republic of Germany or from the Regu	llations of			

According to 91/155/EWG Series 700-032 Date of issue / revised : 09-11-2005

Page 3 of 4

	RESPIRATORY If the solvent vapour concentration exceed the exposure limits, the use of breathing						
	PROTECTION	apparatus is practical or necessary (breathing protection measures)					
	SKIN PROTECTION	Use protective gloves, e.g. Neoprene. At lasting or repeated contact of the product with the skin, use protecting emulsions. Observe recommendations of th manufacturer. After washing hands replace lost skin fat by fat containing skin creams					
	EYE PROTECTION Safety glasses as protection against splashes of solvents should be worn.						
	BODY PROTECTION	ODY PROTECTION Cotton or cotton/synthetic overalls or coveralls are normally suitable. Personal shou wear antistatic clothings made of natural fiber or of high temperature resistates synthetic fiber. All parts of body should be washed after contact.					
9. PHYSICAL AND CHEMICAL PROPERTIES							
	Form	liquide					
	Color	transparent					
	Odour	like solvents Value Unit Method					
	Boiling point	> 140 °C					
	Flash point	> 45 °C					
	Viscosity	2,9 mPas (23°C)					
	Density	0,99 g/cm ³ (23°C)					
	pH-Value	n.a.					
	Content of solver	t < 80 Weight-%					
	Explosion limit	Lower 0,7 Upper 7,5 Vol% (solvent)					
	Solubility in wate	r None at 23 °C					
10.	. STABILITY AND REACTIVITY						
	STABILITY	Stable under the recommended storage and handling conditions (see Section 7).					
	CONDITIONS TO AV	to prevent the possibility of exothermic reaction.					
	DANGEROUS PROD OF DECOMPOSITION						
11.	TOXICOLOGICAL INFORMATION						
	There is no data available on the product itself. It is formulated within the SBPIM's guidelines on materials for exclusion from printing inks and varnishes. Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the rental and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme casas loss of consciousness. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.						
12.	ECOLOGICAL I	NFORMATION					
	be deposited where	ilable on the product itself. The product should not be allowed to enter drains or water courses o it can affect ground or surface waters. The Air Pollution Control requirements of regulations made ntal Protection Act may apply to the use of this product.					
13.							
	WASTE KEYS	VVS-code1222CountrySwitzerlandWaste key (acc.TA-Abfall)55370CountryGermanyWaste key080302CountryEC					
	PACKAGING	The container and packaging materials are recycable according to the local prescriptions and					

According to 91/155/EWG Series 700-032

Date of issue / revised : 09-11-2005

Page 4 of 4

14.	TRANSPORT INFORMATIONS						
	Declarations according to the transport regulations for road (ADR), rail (RID), sea (IMO) and air (ICAO / IATA) transport.						
	LAND TRANSPORT	UN Number : 1210 3					
		Transp. Designations: printing ink related material					
		Package group : III					
	MARITIME TRANSPORT	UN Number : 1210 IMO-Class 3.3 EmS-Nr. F-E, S-D					
		Transp. Designations Printing ink related material					
		Package group III Warning 3					
		Marine pollutant no					
	AIR TRANSPORT	UN Number : 1210 IATA/ICAO-Class 3					
		Transp.Designations Printing ink related material					
		Package group III					
15.	REGULATORY INI	FORMATION					
	CLASSIFICATION ACC	CORDING TO EEC DIRECTIVES					
	DANGER SYMBOL	Xn, N					
	DANGER DESIGNATION						
	HAZARD DETERMINING						
	COMPONENTS OF LAB						
	R-PHRASES 10	Flammable					
	65	Harmful: may cause lung damage if swallowed					
	51/53	Toxic for aquatic organisms, may cause long-term adverse effects in the					
		aquatic environment					
	20	Harmful by inhalation					
	S-PHRASES 16	Keep away from sources of ignition – No smoking					
	25	Avoid contact with eyes					
	29	Do not empty into drains					
	33	Take precautionary measures against static discharges					
		CORDING TO BAG (SWITZERLAND) AND GERMAN DIRECTIVES					
	CH-GIFTGESETZGEBUN						
		TA-Luft I % II 80 % III % VbF-class II BVD-class N.E. %					
	BRANDSCHUTZ WASSERHAUSHALT	VbF-class II BVD-class N.E. WGK (self-assessment) CH 2 BRD 2					
		VEX (Self-assessment) CF 2 BKD 2					
		HEALTH AND SAFETY LEGISLATIONS. THE PROVISION OF THE HEALTH AND SAFETY AT WORK ETC.					
		JESTANCES HAZARDOUS TO HEALTH REGULATIONS APPLY TO THE USE OF THIS PRODUCT AT WORK LTC.					
16.	OTHER INFORMATIONS						
	See also Section 15, R-Phrases						
	R10 Flammable						
	R20 Harmful by inhalation						
	R51/53 Toxic for aquatic organisms, may cause long-term adverse effects in the aquatic environment						
	R65 Harmful; may	cause lung damage if swallowed					
THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET IS PROVIDED IN ACCORDANCE WITH THE REQUIREMENTS OF THE CHIP REGULATIONS. THE PRODUCT SHOULD NOT BE USED FOR PURPOSES OTHER THAN THOSE SHOWN IN SECTION 1 WITHOUT FIRST REFERRING TO THE SUPPLIER AND OBTAINING WRITTEN HANDLING INSTRUCTIONS. AS THE SPECIFIC CONDITIONS OF USE OF THE PRODUCT ARE OUTSIDE THE SUPPLIER'S CONTROL, THE USER IS RESPONSIBLE FOR ENSURING THAT THE REQUIREMENTS OF RELEVANT LEGISLATION ARE COMPLIED WITH. THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET IS BASED ON THE PRESENT STATE OF KNOWLEDGE AND CURRENT NATIONAL LEGISLATION. IT PROVIDES GUIDANCE ON HEALTH, SAFETY AND ENVIRONMENTAL ASPECTS OF THE PRODUCT AND SHOULD NOT BE CONSTRUED AS ANY GUARANTEE OF TECHNICAL PERFORMANCE OR SUITABILITY FOR PARTICULAR APPLICATIONS.							